

MODUX 1 SPIKE

By LuxR OUTDOOR


The Modux 1 Spike luminaries are miniature spotlights with a swivel bracket that provides 45° elevation adjustment.

PROJECT

TYPE

NOTES





GENERAL SPECIFICATIONS

-	
LED	1 W
LUMENS	80 Lm
EFFICACY	80 Lm / W
COLOUR TEMPERATURE	2700K 3000K 4000K
MATERIAL	Natural Copper Stainless Steel Powder Coated Aluminium
FINISH	Black, Copper, Stainless Steel
BEAM	15°, 30°, 53°, 50+17°
CRI	90+
IP	68
WARRANTY	10 Years: Copper & Stainless Steel 5 Years: Electronics & Aluminium
ORIGIN	New Zealand

POWER SPECIFICATIONS


DRIVER	SERIES WIRING	350mA Constant Current (Remote)
DRIVER	PARALLEL WIRING	12VAC (Integral) Remote 12V Transformer Required
		24VDC (Integral) Remote 24V Driver Required

PRODUCT CODES (SERIES WIRING)

BLACK	128-M1SPRABK1530BS	
COPPER	128-MISPRC1530BS	
STAINLESS STEEL	128-MISPRS1530BS	
PARALLEL WIRING AVAILABLE UPON REQUEST		

SERIES WIRING

INPUT 240VAC OUTPUT DC Constant Current



PARALLEL WIRING

INPUT 240VAC OUTPUT 12VAC | 24VDC

