



radiantlighting®

AGO UP POWER

By LOMBARDO


OUTDOOR + WALL

Suitable for ceiling installation for indoor and outdoor use. Anodised or painted aluminium housing (white finish). High resistance to oxidation thanks to anodising treatment. Screen-printed tempered glass diffuser. Black anodised aluminium base

PROJECT

TYPE

NOTES



GENERAL SPECIFICATIONS

| | |
|--------------------|---|
| LED | 10 W |
| LUMENS | 1100 Lm |
| EFFICACY | 110 Lm / W |
| COLOUR TEMPERATURE | 3000K |
| MATERIAL | Anodised Aluminium Serigraphed Glass |
| FINISH | Grey, Black, Brown, White |
| BEAM | 65° |
| IP | 65 |
| CRI | 80 |
| COLOUR DEVIATION | SDCM ≤ 2 |
| WARRANTY | 3 Years |
| ORIGIN | Italy |

POWER SPECIFICATIONS

| | |
|---------|-------------------|
| DRIVER | Integrated |
| DIMMING | Phase-Cut Dimming |
| VOLTAGE | AC DIRECT |

PRODUCT CODES

| | |
|------------|---------------|
| GREY, 65° | 48-LL12650GL3 |
| BLACK, 65° | 48-LL12650BL3 |
| BROWN, 65° | 48-LL126505L3 |
| WHITE, 65° | 48-LL12650WL3 |