LITE 108 (IP 65)

The high-performance FAZE LITE 108 features the latest in LED technology with high lumen per watt efficacy and visually dynamic illumination.



FEATURES



Featuring an IP 65 rating. An ideal pick for situations both indoors and outdoors, providing reliable performance in the face of harsh weather conditions.

- + Precision Reflector With Clear Lens For Better Light Distribution.
- + Specially Designed Heat Sink - For Class Leading Heat Dissipation.
- IC-4 Rated. +
- Multiple Driver Options Perfect For Getting The Light You Want.



LUMINAIRE OPTIONS **LED Options** 12W STANDARD 10W 1060 lm (3000K) 860 lm (3000K) 1130 lm (4000K) 880 lm (4000K) **Beam Options** 36°

60° STANDARD

| GENERAL SPECIFICATIONS | | |
|------------------------|------------------------------------|--|
| Efficacy | Up to 94 lm/W | |
| Colour Temperature | 3000K, Warm White4000K, Cool White | |
| Material | Powder Coated Aluminium | |
| Finish | White Black | |
| CRI | 92+ | |
| IP | 65 | |
| Colour Deviation | SDCM ≤2 | |
| UGR | <23 | |
| Lifetime | >55,000hrs L80 B10 | |
| Warranty | 5 Years | |


PROJECT DETAILS

PROJECT:

TYPE:

NOTES:

DIMENSIONS



| DRIVER SPECIFICATIONS | | |
|-----------------------|--|--|
| Dimensions | L 104 x W 43 x H 24 | |
| Power | 300mA 250mA 240V Remote Dimmable Driver | |
| Dimming | Phase Cut Dimming | |
| Power Factor | > 0.90 | |

DALI Dimming Available Upon Request

| PRODUCT CODES | | |
|---------------------|------------------|--|
| White, 3000K, IP 65 | 118-LI2L12W603IP | |
| Black, 3000K, IP 65 | 118-LI2L12B603IP | |
| White, 4000K, IP 65 | 118-LI2L12W604IP | |
| Black, 4000K, IP 65 | 118-LI2L12B604IP | |

REFLECTOR CODES

36° Reflector

118-RFLLL36



