


EDGE WALL WASHER

The Edge Wall Washer has been specifically designed with an angled silhouette, for the ideal purpose of washing walls with light. Available in 60°, 36°, 24° or 15° beam angles, the Edge Wall Washer provides a variety of lighting options suitable for any project.

- Adjustable head up to 25°.
- Precision reflector – for better light distribution.
- Specially designed heat sink – for class leading heat dissipation.
- Deep set lamp position – for visual comfort and glare reduction.
- Available in powder coated black or white.



DIMENSIONS **W** Ø100 mm **H** 115 mm
CUT-OUT **i** Ø92mm

LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K | 4000K)

13W 1270lm | 1320lm **10W** 1105lm | 1150lm **8W** 960lm | 1000lm

BEAM OPTIONS

60° **STANDARD** 36° 24° 15°

FINISHES

WHITE BLACK

GENERAL SPECIFICATIONS

EFFICACY Up to 125 Lm/W

COLOUR 3000K, Warm White
4000K, Cool White

MATERIAL Powder Coated Material

CRI 92+

IP 44

COLOUR DEVIATION SDCM ≤2

UGR <19

LIFETIME > 55,000hrs L80B10

WARRANTY 7 Years

DRIVER SPECIFICATIONS

DIMENSIONS L 104 x W 43 x H 24mm

POWER 350mA | 300mA | 250mA
240V Remote Flicker Free
Dimmable Driver

DIMMING Phase Cut Dimming

POWER FACTOR > 0.90

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

White, 3000K, 60° **118-ED2A13W603**
 White, 4000K, 60° **118-ED2A13W604**
 Black, 3000K, 60° **118-ED2A13B603**
 Black, 4000K, 60° **118-ED2A13B604**

ACCESSORIES

36° Reflector **118-RFLP36**
 24° Reflector **118-RFLP24**
 15° Reflector **118-RFLP15**

DRIVER CODES

13W **118-350MA**
 11W **118-300MA**
 8W **118-250MA**

DALI DIMMING AVAILABLE UPON REQUEST

